

Information

HiPath 3000 Manager C HiPath 3000 Administration

HiPath 3000 Manager C enables the customer to carry out administration tasks himself. HiPath 3000 Manager C provides network-wide administration of all HiPath 3000 in a central location, the administration of all customer data in a central database and straightforward configuration, relocation and modification of the subscriber across the entire network.

HiPath 3000/5000 Manager C allows to administer, save and print the following customer data:

- optiPoint family, OpenStage family
 - key beep on/off
- Key programming
 - programming freely assignable keys on the system telephone and key modules
- IP Workpoints
 - administration of login names and passwords
- Subscribers
 - names (up to 16 characters)
 - Authorizations for features, such as external call forwarding, override, DISA authorizations
- HiPath Cordless Office (CMI)
 - registration of subscribers
- Telephone lock
 - telephone lock code (5 digits)
 - PIN code for Cordless users
- Display language
 - language per station
- Display names (company logo)
 - change of company name in display
- Entry VoiceMail (EVM)
 - set-up, assignment of mailboxes
 - installation of individual announcements (wave files)
- Attendant console
 - max. number of queued calls
- Hotline
 - type
 - hotline destinations
- Numbering plan
 - defining the internal call number
- Change names of MULAP groups
- Account codes
 - ACCT input
 - type of check
- Call pickup
 - defining stations in the call pickup groups
- Automatic night service
- Least Cost Routing (LCR)
 - changing dialing and time plans (to take advantage of cheap Call by Call providers)
- UCD groups (Integr. Call Center)
 - configuration of group members (agents) and waiting times
- Call forwarding destinations for stations and groups
- Configuration of groups and hunt groups
- Trunk access assignment and modification
- System speed dialing
 - input, modification, deletion of destinations (max. 27 digits)
 - input of names for destinations
 - import/export in standard file format
- Advisory/text messages
 - editing system texts
- Call charge data format
 - call charge multiplier
 - currency format
- Call charges
 - call charge prompt per subscriber/line
 - printout
 - export to file
- Languages for the user interface: German, English, French, Italian, Spanish, Portuguese, Dutch, Danish, Swedish, Finnish, Polish, Hungarian, Russian, Greek

Minimum PC requirements:

- 300 MB free on hard disk
- 512 MB RAM
- VGA monitor (800 x 600)
- 1 unused V.24 interface, S₀ card or network card

Operating system:

- Microsoft Windows 2000/2003
- Microsoft Windows XP
- Microsoft Vista 32/64 Bit

Connection to the communication platform:

- Via V.24 interface
- Via S₀ interface
- TCP/IP interface
- Remote access via:
 - Analog modem
 - ISDN

Scope of delivery

The package supplied includes a CD-ROM with installation instructions in German and English.

Updates

Updates are issued regularly on CD-ROM.

Compatible systems

- All HiPath 3000
- HiPath 5000 RSM.

©Siemens Enterprise Communications GmbH & Co. KG

Siemens Enterprise
Communications GmbH & Co. KG
is a Trademark Licensee of Siemens AG

Hofmannstr. 51
81359 Munich, Germany

The information provided in this brochure contains merely general descriptions or characteristics of performance which in case of actual use do not always apply as described or which may change as a result of further development of the products. An obligation to provide the respective characteristics shall only exist if expressly agreed in the terms of contract. Availability and technical specifications are subject to change without notice. OpenScape, OpenStage and HiPath are registered trademarks of Siemens Enterprise Communications GmbH & Co. KG. All other company, brand, product and service names are trademarks or registered trademarks of their respective holders.

Printed in Germany.